

SENCO[®]MAKING HARD WORK
EASIER**DS522-18V**

Applications

Drywall (to wood or steel studs), Cement board, Underlayment, Sheathing to steel, Metal framing, Structural steel decking, Rigid foam insulation


Features & Benefits

- Patented corner-fit feed system
- Detachable feed system to expose bit for quick reversing
- Selectable 2500/1600 RPM high torque brushless motor
- Precise depth of drive adjustment with depth lock
- Quick slide button bit change
- Variable speed trigger with lock and reverse

Technical specifications

Dimension (LxWxH)	372x86x243 mm
Net weight	2,48 kg
Sound pressure level (Lpa)	63,5 dB
Sound power level (Lwa)	74,5 dB
Vibration level	1,1 m/s ²
Magazine capacity	50 pieces
Battery type	Li-Ion
Battery voltage	18 V
Battery ampere rating	3 Ah
Battery power	54 W
Recharge time 80%	15 minutes
Recharge time 100%	45 minutes
Shots per charge	2000
Number of batteries in kit	2 pieces
Voltage (ac)	230 V
Frequency	50 Hz
Electrical plug type	Continental
Rotations per minute (RPM)	2500 RPM

Fastener specification



Description

DS522-18V, DuraSpin Screwdriver

Art. Nr.

10B2001N

EAN code

8715274245188