

DS722-18V

Duraspin Screwdriver















Applications

Sheathing to wood, sheathing to steel, wood decking, composite decking, rigid foam insulation, cement board, underlayment and flooring, drywall to wood, drywall to steel, fiberglass backed gypsum sheathing, metal framing, structural steel decking

Features & Benefits

Patented corner-fit feed system
 Detachable feed system to expose bit for quick reversing

Selectable 2500/1600 RPM high torque brushless motor

Precise depth of drive adjustment with depth lock Quick slide button bit change

Variable speed trigger with lock and reverse

Technical specifications		
Dimension (LxWxH)	419,5x86x243 mm	
Net weight	2,7 kg	
Sound pressure level (Lpa)	63,5 dB	
Sound power level (Lwa)	74,5 dB	
Vibration level	1,1 m/s²	
Magazine capacity	50 pieces	
Battery type	Li-Ion	
Battery voltage	18 V	
Battery ampere rating	3 Ah	
Battery power	54 W	
Recharge time 80%	15 minutes	
Recharge time 100%	45 minutes	
Shots per charge	2000	
Number of batteries in kit	2 pieces	
Voltage (ac)	230 V	
Frequency	50 Hz	
Electrical plug type	Continental	
Rotations per minute (RPM)	2500 RPM	

Fastener specification



Description	Art. Nr.	EAN code
DS722-18V, DuraSpin Screwdriver	10C2001N	8715274245218